

PACKING DETAILS

Dimensions (mm)	No. of Tiles / Box	Coverage Area
300x600	08	1.44 sq. mtr
150x600	08	0.72 sq. mtr

TECHNICAL SPECIFICATIONS

S.No.	Property	Group B1a-ISO 13006 Annx. G.	Our Value	Test according to
1.	Deviation in length	± 0.6%	± 0.1%	ISO 10545-2
2.	Deviation in thickness	± 5%	± 4%	ISO 10545-2
3.	Straightness of sides	± 0.5%	± 0.1%	ISO 10545-2
4.	Rectangularity	± 0.6%	± 0.1%	ISO 10545-2
5.	Surface flatness	± 0.5%	± 0.15%	ISO 10545-2
6.	Surface quality (%)	A minimum of 95% of the tiles shall be free from visible defects that would impair the appearance of a major area of tile	98% free from visible defects	ISO 10545-2
7.	Scratch Hardness of Surface (Moh's scale)	Min 6	Min 6	ISO 10545-2
8.	Modulus of Rupture	> 35 N/mm ³	40 N/mm ²	ISO 10545-4
9.	Breaking Strength	> 1300 N	> 2000 N	ISO 10545-4
10.	Water absorption	< 0.5%	< 0.2%	ISO 10545-3
11.	Stain resistance	Stain Proof	Stain resistant	ISO 10545-14
12.	Chemical resistance	No damage	No damage	ISO 10545-13
13.	Thermal expansion	< 9 x10 ⁻⁶	< 6 x10 ⁻⁶	ISO 10545-8
14.	Moisture expansion	Nil	Nil	ISO 10545-10
15.	Thermal shock resistance	No damage	No damage	ISO 10545-9
16.	Resistance to surface abrasion	Manufacturer to state abrasion class	PEI class 3-5	ISO 10545-7

- Colours in the catalogue are as accurate as printing process allows, please check actual tiles sample before making final selection.
- Sizes mentioned in the catalogue are the nominal sizes only.
- For better laying please follow the instructions mentioned on the packing box.
- No claim will be entertained once the tiles are fixed.